

Profit from the Eagle Advantage®

Specification Sheet

Short Form Specifications

Eagle worktables, Budget series, model ______. Top to be constructed of heavy gauge type 430 stainless steel with 1% roll on front, 4% backsplash, and sides turned down 90° . Undershelf to be adjustable and constructed of heavy gauge type 430 stainless steel with marine edge. Top reinforced with hat channels and sound deadened. Constructed with uni-lok® patented gusset system with the gussets recessed to reduce lateral movement. Legs to be 1% 0.D., stainless steel, with galvanized gussets and 1" hi-impact plastic bullet feet.



	ıni-lok® System No. 5,165,349)
worktable top sound-deadening tape between channel and top gusset recessed into channel reduces lateral movement "hat" channel frame 12-gauge gusset for 1%" leg is double-welded on backup plate and channel frame for added stability	hat channel and table top are welded together 12-gauge backup plate adds stability — indicates weld point

EAGLE GROUP

100 Industrial Boulevard, Clayton, DE 19938-8903 USA

Phone: 302-653-3000 • Fax: 302-653-2065

www.eaglegrp.com

Foodservice Division: Phone 800-441-8440 MHC/Retail Display Divisions: Phone 800-637-5100

For custom configuration or fabrication needs, contact our **SpecFAB® Division**. Phone: 302-653-3000 • Fax: 302-653-3091 • e-mail: specfab@eaglegrp.com

Item No.:	
Project No.:	
S.I.S. No.:	

Worktables with Backsplash and Stainless Steel Base with Undershelf —Budget Series

	_	_		_
IVI	n	I)	ы	\ S

□ <i>T2424SB-BS</i>	□ <i>T24108SB-BS</i>	□ <i>T3072SB-BS</i>	□ <i>T3660SB-BS</i>
□ <i>T2430SB-BS</i>	□ <i>T24120SB-BS</i>	□ <i>T3084SB-BS</i>	□ <i>T3672SB-BS</i>
□ <i>T2436SB-BS</i>	□ <i>T24132SB-BS</i>	<i>□T3096SB-BS</i>	<i>□T3684SB-BS</i>
□ <i>T2448SB-BS</i>	□ <i>T24144SB-BS</i>	□ <i>T30108SB-BS</i>	□ <i>T3696SB-BS</i>
□ <i>T2460SB-BS</i>	□ <i>T3030SB-BS</i>	□ <i>T30120SB-BS</i>	□ T36108SB-BS
□ <i>T2472SB-BS</i>	□ <i>T3036SB-BS</i>	□ <i>T30132SB-BS</i>	□ T36120SB-BS
□ <i>T2484SB-BS</i>	□ <i>T3048SB-BS</i>	□ <i>T30144SB-BS</i>	□ T36132SB-BS
□ <i>T2496SB-BS</i>	□ <i>T3060SB-BS</i>	<i>□T3648SB-BS</i>	□ <i>T36144SB-BS</i>

Tabletop

- Patented uni-lok® gusset system (patent #5,165,349): gussets are recessed into hat channel, reducing lateral movement.
- Top reinforced with welded-on hat channel.
- Sound-deadened between top and channels.
- 4½" (114mm)-high 90° backsplash with 1" (25mm) turn at 90°.
- 1½" (38mm)-diameter 180° rolled edge on front. Ends are turned down 90°, providing for flush installations when required.
- Heavy gauge type 430 polished stainless steel.

Adjustable Undershelf

- Easy assembly to legs: Snap split sleeves onto the grooved legs, and slide undershelf over the split sleeves, creating a positive lock between undershelf and legs.
- Heavy gauge stainless steel.
- Gusset welded to each corner.
- · Heavy duty marine edge design.

Legs—1½" (41mm)-diameter

- Tables 96" (2438mm) and longer come with six legs or more.
- Heavy gauge stainless steel.
- 1" (25mm) adjustable hi-impact plastic feet.

Options / Accessories

- ☐ Drawer☐ Lock☐
- ☐ Casters
- Stainless steel bullet feet
- Overshelves
- Duplex receptacles
- ☐ Pot rack
- ☐ Sink
- Additional undershelfStabilizer Bar (for 30"
 - and 36"-wide tables)









EG10.45A Rev. 03/09




Item No.:	
Project No.:	
S.I.S. No.:	

Worktables with Backsplash and Stainless Steel Base with Undershelf—Budget Series







	# of	width		length		wei	weight	
model #	legs	in.	mm	in. `	mm	lbs.	kg	
T2424SB-BS	4	24"	610	24″	610	43	19.5	
T2430SB-BS	4	24"	610	30″	762	48	21.8	
T2436SB-BS	4	24"	610	36″	914	53	24.0	
T2448SB-BS	4	24″	610	48″	1219	63	28.6	
T2460SB-BS	4	24″	610	60″	1524	73	33.1	
T2472SB-BS	4	24″	610	72″	1829	85	38.6	
T2484SB-BS	4	24″	610	84″	2134	97	44.0	
T2496SB-BS	6	24"	610	96″	2438	114	51.7	
T24108SB-BS T24120SB-BS	6	24"	610	108″	2743	142	64.4	
T24132SB-BS	6 8	24″ 24″	610 610	120″ 132″	3048 3353	154 166	69.9 75.3	
T241323B-BS	8	24"	610	144"	3658	178	80.7	
T3030SB-BS	4	30″	762	30″	762	50	22.7	
T3036SB-BS	4	30″	762	36″	914	53	24.0	
T3048SB-BS	4	30″	762	48″	1219	70	31.8	
T3060SB-BS	4	30″	762	60″	1524	81	36.7	
T3072SB-BS	4	30″	762	72″	1829	94	42.6	
T3084SB-BS	4	30″	762	84″	2134	108	49.0	
T3096SB-BS	6	30″	762	96″	2438	130	59.0	
T30108SB-BS	6	30″	762	108″	2743	150	68.0	
T30120SB-BS	6	30″	762	120″	3048	170	77.1	
T30132SB-BS	8	30″	762	132″	3353	188	85.3	
T30144SB-BS	8	30″	762	144″	3658	207	93.9	
T3648SB-BS	4	36″	914	48″	1219	77	34.9	
T3660SB-BS	4	36″	914	60″	1524	90	40.8	
T3672SB-BS	4	36"	914	72″	1829	106	48.1	
T3684SB-BS	4	36"	914	84″	2134	123	55.8	
T3696SB-BS	6	36"	914	96″	2438	132	59.9	
T36108SB-BS	6	36″	914	108″	2743	169	76.7	
T36120SB-BS	6	36"	914	120"	3048	192	87.1	
T36132SB-BS	8	36″	914	132″	3353	216	98.0	
T36144SB-BS	8	36″	914	144″	3658	239	108.4	

ما الله أدده

EAGLE GROUP

100 Industrial Boulevard, Clayton, DE 19938-8903 USA

Phone: 302-653-3000 • Fax: 302-653-2065

www.eaglegrp.com

Foodservice Division: Phone 800-441-8440

MHC/Retail Display Divisions: Phone 800-637-5100

Printed in U.S.A. ©2009 by Eagle Group

Rev. 03/09